APTC SEALANTS GUIDE
CONSTRUCTION SEALANTS

PROFLEX HY | PROFLEX MS | PROFLEX FC PU



APTC Proflex HY is a high performance, one component, construction sealant based on hybrid technology.

Available colours

BEIGE | BLACK | BRONZE | CONCRETE GREY | EPPING GREY | LIGHT BROWN | MIDNIGHT | OFF WHITE | REDWOOD | SANDSTONE | WHITE

AREAS OF USE

- Construction sealant for building joints requiring a high movement sealant up to +/- 25%
- Expansion joints in brickwork and concrete
- Joint sealant underneath compatible water based or acrylic waterproofing membranes

SUBSTRATES

Concrete, precast & tilt panels, render, brick and blockwork, plasterboard, fibre cement sheet, aluminium windows, stainless steel, fibreglass and painted wood.



APTC Proflex MS is an advanced MS Polymer based elastomeric sealant designed for sealing applications.

Available colours

AMBER | BLACK | CONCRETE GREY | MISTY GREY | OFF WHITE | PANEL GREY | SANDSTONE | TOKYO BEIGE | WHITE

AREAS OF USE

- Wall to wall and wall to floor junctions
- Perimeter sealing of doors and windows in buildings
- Waterproofing joint sealant underneath compatible water based membranes

SUBSTRATES

Glass, PVC, aluminium, concrete, brick, most metals, polyester coatings and some plastics



Available in Grey only

APTC Proflex FC PU is a high performance, fast curing polyurethane sealant and adhesive

AREAS OF USE

- Sealant for construction and expansion joints, floor and concrete joints and perimeter sealing of door and window frames
- Adhesive—for building and construction applications

SUBSTRATES

Concrete, most metals, natural stone, bricks, block, GRC and fibreglass

Suitable for trafficable, pick resistant and chemical resistant areas

Product colours shown are a digital representation only. Contact the sales team for a full product sample chart

APTC Australia
P | 1300 394 239 **W |** www.aptcaust.com.au
ABN 61 058 678 961

For all sealant specifications and technical advice please contact APTC Australia 1300 394 239