

SPORTS SURFACES

DATA SHEET

PAVISINT LINE

**A two-component paste for smoothing
laying surfaces in prefabricated rubber mats**

CHARACTERISTICS

Pavisint Line is a highly covering polyurethane paint, especially developed to mark field lines on polyurethane, PVC, EPDM, rubber and linoleum surfaces.

APPEARANCE

Component A: medium-viscosity pigmented liquid.
Component B: transparent low-viscosity liquid.

CHARACTERISTICS OF THE LIQUID PRODUCT

Characteristic	U.M.	Value	Tolerance
Specific weight	Kg/dm ³	1,27	± 0,1
Dry mass residue	%	63	± 3
Dry volume residue	%	50	± 3
Residue at 450°C	%	25	± 3
Mixing ratio A:B	-	A:B = 78:22	-

LAYING INSTRUCTIONS

Toolings	Thinner	Type of thinner	Cleaning method
Roller	Ready for use	-	DIL MS1
Brush	Ready for use	-	DIL MS1

LAYING SURFACE

Polyurethane, PVC, EPDM, rubber and linoleum sports surfaces. When applying on old surfaces, clean the deck thoroughly and verify whether it is necessary to roughen the deck to ensure adhesion.

IMPORTANT: resin surfaces are generally waterproof (non-draining) so that the deck must be sloped correctly to ensure rainwater runoff and prevent pooling. Works to correct the deck must be carried out before laying the final covering; if necessary please contact the Technical Office of CASALI S.p.A.

CONSUMPTION

Consumption varies according to the use of the court: to mark in the lines of volley ball and tennis courts use the 5 kg. tin while for basket ball, 5-A-Side Soccer or handball courts use the 10 kg tin of Pavisint Line.

APPLICATION INSTRUCTIONS

Ambient temperature: MIN 10°C - MAX 40°C
Ambient relative humidity: MAX 80 %
Laying surface temperature: MIN 10°C - MAX 45°C

CASALI
SPORT



Rev. 01/2013

SPORTS SURFACES

PAVISINT LINE

DATA SHEET

HARDENING AT 23°C AND 50% U.R.

Pot life	1 h
To touch	4 h
Interval between coatings	MIN 20 h - MAX 36 h
Complete hardening time	5 days

PACKAGING INSTRUCTIONS

Colours available	White, yellow and other on request.
Packaging	A + B = 2,5 kg

STORAGE INSTRUCTIONS

Storage temperature:	MIN 10°C - MAX 40°C
Stability in the original package:	6 months

IMPORTANT INSTRUCTIONS

Do not apply the product in the case of fog, high humidity levels, rain or frost. The conditions of the deck must be checked to ensure that it is plane, resistant, consistent that the granule grading is correct in order to prevent imperfections on the surface. Repairs and/or filling must be carried out according to the specifications of Casali S.p.A. Check for rising dampness and/or infiltrations, if necessary contact the Technical Office of Casali S.p.A.

SAFETY STANDARDS

Please read the safety data sheet carefully before using this product.

*The data provided by these data sheets are approximate and the Company reserves the right to modify the same for technical reasons, without prior notice. The solutions proposed do not represent all the possible uses but are merely case studies deriving from Casali's installation experience and are therefore intended only for purposes of illustration. The user is exclusively responsible for the way the products illustrated are used, whether properly or improperly, for evaluating in advance the suitability or otherwise of the product for its requirements and exerting the utmost caution in handling chemical products. **Important: to ensure best colour uniformity of surface laid products, we recommend that you use materials from the same production lot as finishing layer. The Technical Office of Casali's Synthetics Division is at your complete disposal for any further specific information or explanations you may require (phone 071 9162095).***

CASALI
SPORT



ο ΕΠΙΧΕΙΡΗΣΙΑΣ