



APTC PVC PROTECTION TAPE

Technical Data Sheet

PRODUCT DESCRIPTION:

A 115 micron PVC tape with a coating of rubber based pressure sensitive adhesive on one side. The product adheres well to both glass and aluminium, and removes cleanly with no adhesive residue.

FEATURES:

Medium tack providing a staple adhesive strength. Excellent weather ability and UV resistant for up to 6 months.

APPLICATIONS:

Ideal for protection of:

- Aluminium frames during transportation and installation.
- A wide variety of metals, painted steel and sheeting.
- Construction - particularly where bricklaying or rendering is involved.



TECHNICAL DATA:

Tape Colour	Black
Tape Thickness	0.120mm
Adhesion to Steel	0.11 kg/cm
Elongation at break	150%
Tensile Strength	2.0 kg/cm

PACKAGING & STORAGE:

Standard Sizes: 24mm x 66m, 36mm x 66m, 44mm x 66m, 48mm x 66m, 60mm x 66m, 72mm x 66m and available in custom widths up to 1m wide.

DISCLAIMER:

This product should be applied to a clean and dry surface. The adhesive of the product must not be exposed to direct sunlight when applied. The above figures represent average values. Tape should be stored at room temperature and should not be exposed to sunlight. Please Note: Recommendation and advice regarding the use of this product is to be taken as a guide only and APTC Australia shall not be liable for any inaccuracy in the information or for any loss, injury or damage whatsoever resulting from its use. To the full extent permitted by law, APTC Australia's liability is limited at its discretion, to the replacement of the goods or the supply of equivalent goods.



Manufactured for:

APTC Australia Pty Ltd

18—22 Pacific Drive
Keysborough Vic 3173
Tel: 1300 394 239

275 Macaulay Road
North Melbourne Vic 3051
Fax: 1300 394 279

www.aptecaust.com.au