

SAFETY DATA SHEET

DOW CHEMICAL (AUSTRALIA) PTY LTD

Product name: DOWSIL™ 580 (AUS) Glass, Metal and Masonry Issue Date: 31.03.2020

Sealant Grey

Print Date: 01.04.2020

DOW CHEMICAL (AUSTRALIA) PTY LTD encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1: IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product name: DOWSIL™ 580 (AUS) Glass, Metal and Masonry Sealant Grey

Recommended use of the chemical and restrictions on use

Identified uses: Adhesive, binding agents

COMPANY IDENTIFICATION

DOW CHEMICAL (AUSTRALIA) PTY LTD LEVEL 29 367 COLLINS STREET MELBOURNE VIC 3000 AUSTRALIA

Customer Information Number: 1800-780-074

SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER 24-Hour Emergency Contact: 1800-033-882

Local Emergency Contact: 1800-033-882

For advice, contact a doctor (at once) or the Australian Poisons Information Centre: 131 126

Transport Emergency Only Dial 000

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Classification

Skin sensitisation - Category 1

GHS label elements Hazard pictograms



Signal word: WARNING!

Sealant Grey

Hazard statements

May cause an allergic skin reaction.

Precautionary statements

Prevention

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves.

Response

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/ attention.

Wash contaminated clothing before reuse.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

SECTION 3: COMPOSITION AND INFORMATION ON INGREDIENTS, IN **ACCORDANCE WITH SCHEDULE 8**

This product is a mixture.

Component	CASRN	Concentration
Calcium carbonate treated with stearic acid	Not available	>= 37.0 - <= 47.0 %
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 5.0 - <= 6.0 %
Silicon dioxide	7631-86-9	>= 4.0 - <= 5.0 %
2-Butanone, O,O',O"- (methylsilylidyne)trioxime	22984-54-9	>= 3.0 - <= 4.0 %
N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine	1760-24-3	>= 0.71 - <= 0.72 %
Quartz	14808-60-7	>= 0.41 - <= 0.42 %

Sealant Grey

Methyltri(ethylmethylketoxime)sila Not available

<= 0.3822 %

Issue Date: 31.03.2020

ne isomers and oligomers

Vinyltri (methylethylketoxime) 2224

2224-33-1

>= 0.29 - <= 0.3 %

silane

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: No emergency medical treatment necessary.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation or rash occurs. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5: FIREFIGHTING MEASURES

Hazchem Code

None Allocated

Extinguishing media

Suitable extinguishing media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing media: None known...

Special hazards arising from the substance or mixture

Sealant Grey

Hazardous combustion products: Carbon oxides. Silicon oxides. Nitrogen oxides (NOx). Metal oxides. Formaldehyde.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health..

Advice for firefighters

Fire Fighting Procedures: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

See sections: 7, 8, 11, 12 and 13.

SECTION 7: HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

Precautions for safe handling: Do not get on skin or clothing. Do not swallow. Avoid contact with eyes. Protect from moisture. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Store in accordance with the particular national regulations.

Issue Date: 31.03.2020

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: Do not store in or use iron or steel containers.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Calcium carbonate treated	Dow IHG	TWA	1 mg/m3
with stearic acid			
	AU OEL	TWA	10 mg/m3 , Calcium
			carbonate
	Further information: a: This crystalline silica	value is for inhalable dust co	ntaining no asbestos and < 1%
Distillates (petroleum),	AU OEL	TWA Mist	5 mg/m3
hydrotreated middle			
Silicon dioxide	Dow IHG	TWA Respirable dust	2 mg/m3
	Dow IHG	TWA Total dust	6 mg/m3
	AU OEL	TWA Respirable dust	2 mg/m3
N-(3-(Trimethoxysilyl)	Dow IHG	•	See Further information
propyl)-1,2-ethanediamine			
	Further information: Skin Sensitizer		
Quartz	ACGIH	TWA Respirable	0.025 mg/m3 , Silica
		particulate matter	
	Further information: lung cancer: Lung cancer; pulm fibrosis: Pulmonary fibrosis; A2: Suspected human carcinogen		
	AU OEL	TWA Respirable dust	0.1 mg/m3
Methyl Ethyl Ketoxime	US WEEL	TWA	10 ppm
,	Further information: DSEN: Dermal Sensitization Notation		
	Dow IHG	TWA	0.15 ppm
	Further information: Skin S	ensitizer	

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing:

Methyl ethyl ketoxime

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). Skin protection

> Hand protection: Use chemical resistant gloves classified under standard AS/NZS 2161.10: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol

Sealant Grey

("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to AS/NZS 2161.10) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to AS/NZS 2161.10) is recommended. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

Other Information: Selection and use of personal protective equipment should be in accordance with the recommendations in one or more of the relevant Australian/New Zealand Standards, including:

AS/NZS 1336: Eye and face protection – Guidelines.

AS/NZS 1337: Personal eye protection - Eye and face protectors for occupational applications.

AS/NZS 1715: Selection, use and maintenance of respiratory protective equipment.

AS/NZS 2161: Occupational protective gloves. AS/NZS 2210: Occupational protective footwear. AS/NZS 4501: Occupational protective clothing Set

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state paste
Color light grey
Odor slight

Odor Threshold

pH

Not applicable

Melting point/range

Freezing point

Boiling point (760 mmHg)

Flash point

No data available

Not applicable

Not applicable

Issue Date: 31.03.2020

Sealant Grey

Evaporation Rate (Butyl Acetate Not applicable

= 1)

Flammability (solid, gas) Not classified as a flammability hazard

Lower explosion limitNo data availableUpper explosion limitNo data availableVapor PressureNot applicableRelative Vapor Density (air = 1)No data available

Relative Density (water = 1) 1.38

Water solubility No data available Partition coefficient: n- No data available

octanol/water

Auto-ignition temperatureNo data availableDecomposition temperatureNo data availableDynamic ViscosityNot applicableKinematic ViscosityNot applicableExplosive propertiesNot explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Molecular weightNo data availableParticle sizeNo data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

Conditions to avoid: Do not expose to temperatures above 212 °F/100 °C. Exposure to moisture

Incompatible materials: Oxidizing agents

Hazardous decomposition products:

Decomposition products can include and are not limited to: Formaldehyde. Methyl Ethyl Ketoxime.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Exposure routes

Eye contact, Skin contact, Ingestion.

Page 7 of 25

Sealant Grey

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): LD50, Rat, > 5,000 mg/kg Estimated.

Information for components:

Calcium carbonate treated with stearic acid

Single dose oral LD50 has not been determined.

For similar material(s): LD50, Rat, > 2,000 mg/kg No deaths occurred at this concentration.

Distillates (petroleum), hydrotreated middle

LD50, Rat, > 5,000 mg/kg

Silicon dioxide

LD50, Rat, > 5,000 mg/kg

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

LD50, Rat, male and female, 2,463 mg/kg OECD Test Guideline 401

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

LD50, Rat, male and female, 2,295 mg/kg OPPTS 870.1100

Quartz

Single dose oral LD50 has not been determined.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Single dose oral LD50 has not been determined.

Vinyltri (methylethylketoxime) silane

LD50, Rat, > 2,000 mg/kg

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, > 5,000 mg/kg Estimated.

Information for components:

Calcium carbonate treated with stearic acid

The dermal LD50 has not been determined.

Sealant Grey

Distillates (petroleum), hydrotreated middle

LD50, Rabbit, > 3,160 mg/kg No deaths occurred at this concentration.

Silicon dioxide

LD50, Rabbit, > 5,000 mg/kg

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

LD50, Rat, male and female, > 2,000 mg/kg OECD Test Guideline 402 No deaths occurred at this concentration.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

Quartz

The dermal LD50 has not been determined.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

The dermal LD50 has not been determined.

Vinyltri (methylethylketoxime) silane

LD50, Rat, > 2,000 mg/kg

Acute inhalation toxicity

No adverse effects are anticipated from inhalation. As product: The LC50 has not been determined.

Information for components:

Calcium carbonate treated with stearic acid

Dust may cause irritation to upper respiratory tract (nose and throat).

The LC50 has not been determined.

Distillates (petroleum), hydrotreated middle

LC50, Rat, 4 Hour, dust/mist, > 5.2 mg/l

Silicon dioxide

Maximum attainable concentration. LC50, Rat, 4 Hour, dust/mist, > 2.08 mg/l No deaths occurred at this concentration.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

The LC50 has not been determined.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

LC50, Rat, 4 Hour, dust/mist, 1.49 - 2.44 mg/l OECD Test Guideline 403

Quartz

The LC50 has not been determined.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

The LC50 has not been determined.

Vinyltri (methylethylketoxime) silane

Sealant Grey

The LC50 has not been determined.

Skin corrosion/irritation

Based on information for component(s):

Prolonged exposure not likely to cause significant skin irritation.

Information for components:

Calcium carbonate treated with stearic acid

Essentially nonirritating to skin.

May cause drying and flaking of the skin.

Distillates (petroleum), hydrotreated middle

Brief contact may cause slight skin irritation with local redness.

Silicon dioxide

Brief contact is essentially nonirritating to skin.

May cause skin irritation due to mechanical abrasion.

May cause drying and flaking of the skin.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Brief contact may cause slight skin irritation with local redness.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Brief contact may cause moderate skin irritation with local redness.

Quartz

May cause skin irritation due to mechanical abrasion.

May cause drying and flaking of the skin.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Brief contact may cause slight skin irritation with local redness.

Vinyltri (methylethylketoxime) silane

Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

Based on information for component(s):

May cause slight temporary eye irritation.

Information for components:

Calcium carbonate treated with stearic acid

May cause slight temporary eye irritation.

Dust may irritate eyes.

Distillates (petroleum), hydrotreated middle

May cause slight eye irritation.

Silicon dioxide

Solid or dust may cause irritation or corneal injury due to mechanical action.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Sealant Grey

May cause moderate eye irritation.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Quartz

Solid or dust may cause irritation or corneal injury due to mechanical action.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

May cause slight eye irritation.

Vinyltri (methylethylketoxime) silane

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Sensitization

For skin sensitization:

Contains component(s) which have caused allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Information for components:

Calcium carbonate treated with stearic acid

For skin sensitization:

No relevant data found.

For respiratory sensitization:

No relevant data found.

Distillates (petroleum), hydrotreated middle

For similar material(s):

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Silicon dioxide

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Has demonstrated the potential for contact allergy in mice.

For respiratory sensitization:

No relevant data found.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Has caused allergic skin reactions when tested in guinea pigs.

Sealant Grey

Issue Date: 31.03.2020

For respiratory sensitization:

No relevant data found.

Quartz

For skin sensitization:

No relevant data found.

For respiratory sensitization:

No relevant data found.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Vinyltri (methylethylketoxime) silane

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Information for components:

Calcium carbonate treated with stearic acid

Available data are inadequate to determine single exposure specific target organ toxicity.

Distillates (petroleum), hydrotreated middle

Available data are inadequate to determine single exposure specific target organ toxicity.

Silicon dioxide

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Available data are inadequate to determine single exposure specific target organ toxicity.

<u>Quartz</u>

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Available data are inadequate to determine single exposure specific target organ toxicity.

Vinyltri (methylethylketoxime) silane

Available data are inadequate to determine single exposure specific target organ toxicity.

Aspiration Hazard

Sealant Grey

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Calcium carbonate treated with stearic acid

Based on physical properties, not likely to be an aspiration hazard.

Distillates (petroleum), hydrotreated middle

May be fatal if swallowed and enters airways.

Silicon dioxide

Based on physical properties, not likely to be an aspiration hazard.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Based on available information, aspiration hazard could not be determined.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Based on available information, aspiration hazard could not be determined.

Quartz

Based on physical properties, not likely to be an aspiration hazard.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Based on physical properties, not likely to be an aspiration hazard.

Vinyltri (methylethylketoxime) silane

Based on available information, aspiration hazard could not be determined.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains component(s) which have been reported to cause effects on the following organs in animals: Blood

Information for components:

Calcium carbonate treated with stearic acid

Repeated exposures to dusts of this material are not anticipated to result in systemic toxicity or permanent lung injury; however, excessive exposures may cause less severe respiratory effects.

Distillates (petroleum), hydrotreated middle

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Silicon dioxide

No relevant data found.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

For similar material(s):

In animals, effects have been reported on the following organs:

Blood

Sealant Grey

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

In animals, effects have been reported on the following organs: Respiratory tract.

Quartz

In humans, effects have been reported on the following organs: Kidney.

Repeated excessive exposure to crystalline silica may cause silicosis, a progressive and disabling disease of the lungs.

Due to the physical state of the material, this component is not expected to be bioavailable under normal handling and processing conditions.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

For similar material(s):

In animals, effects have been reported on the following organs: Blood

Vinyltri (methylethylketoxime) silane

In animals, effects have been reported on the following organs: Blood.

Carcinogenicity

Based on information for component(s): Did not cause cancer in long-term animal studies which used routes of exposure considered relevant to industrial handling. Positive results have been reported in other studies using routes of exposure not relevant to industrial handling. Contains an additional component(s) that is not expected to be bioavailable due to the physical state of the material under normal handling and processing conditions.

Information for components:

Calcium carbonate treated with stearic acid

No relevant data found.

Distillates (petroleum), hydrotreated middle

For similar material(s): Did not cause cancer in laboratory animals.

Silicon dioxide

No relevant data found.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

No relevant data found.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

No relevant data found.

Quartz

Has caused cancer in humans. Has caused cancer in laboratory animals. Due to the physical state of the material, this component is not expected to be bioavailable under normal handling and processing conditions.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

No relevant data found.

Sealant Grey

Issue Date: 31.03.2020

Vinyltri (methylethylketoxime) silane

No relevant data found.

Teratogenicity

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

Information for components:

Calcium carbonate treated with stearic acid

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

Distillates (petroleum), hydrotreated middle

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

Silicon dioxide

No relevant data found.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Did not cause birth defects in laboratory animals.

Quartz

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

No relevant data found.

Vinvltri (methylethylketoxime) silane

No relevant data found.

Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies.

Information for components:

Calcium carbonate treated with stearic acid

For similar material(s): In animal studies, did not interfere with fertility. In animal studies, did not interfere with reproduction.

Distillates (petroleum), hydrotreated middle

For similar material(s): In animal studies, did not interfere with reproduction.

Silicon dioxide

No relevant data found.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Sealant Grey

In animal studies, did not interfere with fertility. In animal studies, did not interfere with reproduction.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

In animal studies, did not interfere with reproduction.

Quartz

No relevant data found.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

No relevant data found.

Vinyltri (methylethylketoxime) silane

No relevant data found.

Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

Information for components:

Calcium carbonate treated with stearic acid

For similar material(s): In vitro genetic toxicity studies were negative.

Distillates (petroleum), hydrotreated middle

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Silicon dioxide

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Quartz

In vitro genetic toxicity studies were negative in some cases and positive in other cases.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

No relevant data found.

Vinyltri (methylethylketoxime) silane

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Ecotoxicity

Sealant Grey

Calcium carbonate treated with stearic acid

Acute toxicity to fish

No relevant data found.

Distillates (petroleum), hydrotreated middle

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LL50, Scophthalmus maximus (turbot), 96 Hour, > 1,028 mg/l, Test substance: Water Accommodated Fraction

Acute toxicity to aquatic invertebrates

LL50, Acartia tonsa, 48 Hour, > 3,193 mg/l, Test substance: Water Accommodated Fraction

Acute toxicity to algae/aquatic plants

EL50, Skeletonema costatum (marine diatom), 72 Hour, > 10,000 mg/l, Test substance: Water Accommodated Fraction

Toxicity to bacteria

EC50, 3 Hour, > 100 mg/l, OECD Test Guideline 209

Chronic toxicity to aquatic invertebrates

NOELR, Ceriodaphnia dubia (water flea), 8 d, > 100 mg/l, Test substance: Water Accommodated Fraction

Silicon dioxide

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Danio rerio (zebra fish), 96 Hour, 5,000 - 10,000 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, > 1,000 mg/l

Acute toxicity to algae/aguatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Biomass, 440 mg/l

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). For the hydrolysis product(s)

LC50, Oncorhynchus mykiss (rainbow trout), Static, 96 Hour, > 120 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

For the hydrolysis product(s)

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 120 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

For the hydrolysis product(s)

Sealant Grey

EC50, Selenastrum capricornutum (green algae), Static, 72 Hour, Growth rate, 94 mg/l, OECD Test Guideline 201

For the hydrolysis product(s)

NOEC, Selenastrum capricornutum (green algae), Static, 72 Hour, Growth rate, 30 mg/l, OECD Test Guideline 201

Chronic toxicity to fish

NOEC, Oryzias latipes (Orange-red killifish), flow-through test, 14 d, 50 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna, semi-static test, 21 d, > 100 mg/l

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Acute toxicity to fish

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

For the hydrolysis product(s)

LC50, zebra fish (Brachydanio rerio), 96 Hour, 597 mg/l

Acute toxicity to aquatic invertebrates

For the hydrolysis product(s)

EC50, Daphnia magna (Water flea), 48 Hour, 81 mg/l

Acute toxicity to algae/aquatic plants

For the hydrolysis product(s)

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, 8.8 mg/l

For the hydrolysis product(s)

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, 3.1 mg/l

Toxicity to bacteria

For the hydrolysis product(s)

EC50, Pseudomonas putida, 16 Hour, Growth inhibition, 67 mg/l

Chronic toxicity to aquatic invertebrates

For the hydrolysis product(s)

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, > 1 mg/l

Toxicity to Above Ground Organisms

Material is moderately toxic to birds on an acute basis (LD50 between 51 and 500 mg/kg).

Toxicity to soil-dwelling organisms

NOEC, Eisenia fetida (earthworms), 14 d, >= 1,000 mg/kg

Quartz

Acute toxicity to fish

Not expected to be acutely toxic to aquatic organisms.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Acute toxicity to fish

No relevant data found.

Sealant Grey

Vinyltri (methylethylketoxime) silane

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 120 mg/l, OECD Test Guideline 203 LC50, Oryzias latipes (Orange-red killifish), 96 Hour, > 100 mg/l, OECD Test Guideline 203

Persistence and degradability

Calcium carbonate treated with stearic acid

Biodegradability: No relevant data found.

Distillates (petroleum), hydrotreated middle

Biodegradability: Material is expected to be readily biodegradable.

10-day Window: Not applicable

Biodegradation: 74 % Exposure time: 28 d

Method: OECD Test Guideline 306

Silicon dioxide

Biodegradability: Biodegradation is not applicable.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Biodegradability: Based on information for a similar material: This material rapidly

hydrolyzes to products that are either readily or ultimately biodegradable.

10-day Window: Fail **Biodegradation:** 0 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the

material is not biodegradable under environmental conditions.

10-day Window: Fail **Biodegradation:** 39 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A or Equivalent

Theoretical Oxygen Demand: 2.39 mg/mg Estimated.

Chemical Oxygen Demand: 1.76 mg/mg Estimated.

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	23 %
10 d	30 %
20 d	29 %

Stability in Water (1/2-life)

Sealant Grey

Hydrolysis, half-life, 0.025 Hour, pH 7

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals **Atmospheric half-life:** 0.088 d

Method: Estimated.

Quartz

Biodegradability: Biodegradation is not applicable.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Biodegradability: No relevant data found.

Vinyltri (methylethylketoxime) silane

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails

Issue Date: 31.03.2020

to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail **Biodegradation:** 0 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A

Stability in Water (1/2-life)

Hydrolysis, DT50, < 1 min, Half-life Temperature 2 °C, OECD Test Guideline 111

Bioaccumulative potential

Calcium carbonate treated with stearic acid

Bioaccumulation: No relevant data found.

Distillates (petroleum), hydrotreated middle

Bioaccumulation: No relevant data found.

Silicon dioxide

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.53

Bioconcentration factor (BCF): 3.16

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Bioaccumulation: Bioconcentration potential is low (BCF less than 100 or log Pow greater

than 7).

Partition coefficient: n-octanol/water(log Pow): 11.2

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): < 3 estimated

Quartz

Bioaccumulation: Partitioning from water to n-octanol is not applicable.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Bioaccumulation: No relevant data found.

Page 20 of 25

Sealant Grey

Vinyltri (methylethylketoxime) silane

Bioaccumulation: No relevant data found.

Mobility in Soil

Calcium carbonate treated with stearic acid

No relevant data found.

Distillates (petroleum), hydrotreated middle

No relevant data found.

Silicon dioxide

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 21.73

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

No relevant data found.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Expected to be relatively immobile in soil (Koc > 5000).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Issue Date: 31.03.2020

Partition coefficient (Koc): > 5000 Estimated.

Quartz

No relevant data found.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

No relevant data found.

Vinyltri (methylethylketoxime) silane

No relevant data found.

Results of PBT and vPvB assessment

Calcium carbonate treated with stearic acid

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Distillates (petroleum), hydrotreated middle

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Silicon dioxide

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Page 21 of 25

Sealant Grey

Quartz

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Methyltri(ethylmethylketoxime)silane isomers and oligomers

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Vinyltri (methylethylketoxime) silane

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Other adverse effects

Calcium carbonate treated with stearic acid

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

<u>Distillates (petroleum), hydrotreated middle</u>

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Silicon dioxide

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Quartz

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Vinyltri (methylethylketoxime) silane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Page 22 of 25

Sealant Grey

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

SECTION 14: TRANSPORT INFORMATION

ADG

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Consult IMO regulations before transporting ocean bulk

Issue Date: 31.03.2020

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

Hazchem Code None Allocated

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

Poison Schedule

Not Scheduled

Australia Inventory of Chemical Substances (AICS)

All ingredients in this preparation are listed in the Australian Inventory of Chemical Substances, AICS, or are exempt.

Prohibition/Licensing Requirements

: There is no applicable prohibition or notification/licensing requirements, including for

Sealant Grey

carcinogens under Commonwealth, State or Territory legislation.

Issue Date: 31.03.2020

SECTION 16: ANY OTHER RELEVANT INFORMATION

Revision

Identification Number: 4018246 / A142 / Issue Date: 31.03.2020 / Version: 4.1 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
AU OEL	Australia. Workplace Exposure Standards for Airborne Contaminants.
Dow IHG	Dow Industrial Hygiene Guideline
TWA	Time weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx -Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG -Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet: TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

DOW CHEMICAL (AUSTRALIA) PTY LTD urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The

information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.