



UNIVERSAL PRIMER WATER BASED ACRYLIC PRIMER

PRODUCT DESCRIPTION:

Universal Primer is a rapid drying solvent free low VOC water based acrylic primer.

For use over porous and non porous substrates such as ceramic tiles, painted surfaces (waterbased only) and sealed or burnished concrete floors.

For extremely non porous, hard and tight substrates it is recommended that a light grind or sand be conducted to enhance adhesion.

Roberts Universal primer is compatible with cement based ceramic tile adhesives and levelling compounds.

SUBSTRATE:

Universal Primer can be applied internally or externally over clean, dry surfaces.

Sub Floor Preparation:

Subfloor must dry, sound and be free of oil, grease, wax, coatings, curing compounds, dust, old adhesive and any other contamination which could inhibit bond.

Concrete floors must be dry sound, smooth and clean in accordance with current relevant Australian standards. Do not use solvents, or acid etching to clean the subfloor.

Subfloors that display high moisture levels it is recommended a RLA Moisture Barrier product be applied. Do not apply primer if temperature is below 5°C or greater than 35°C

Please ensure substrates such as ceramic tiles, sealed or burnished floors have no coatings or curing compounds residing on the surface before the application of priming. For extremely non porous, hard and tight substrates it is recommended that a light grind or sand be conducted to enhance adhesion.

APPLICATION:

Porous Substrates:

Priming of standard concrete surfaces, dilute 1 part Universal Primer with 2 parts Clean Water

Apply primer using a roller, brush or broom, ensuring entire area is completely primed.

Very absorbent concrete may require a second coat of Universal Primer diluted 1 part Primer with 3 parts Water. Allow to cure for 30 minutes.

Non-porous Substrates:

Apply an even layer of Universal Primer neat (undiluted to non porous substrates).

Allow primer to dry to a clear film (approx. 2 hours @ 23°C). Once Universal Primer is a tack free clear film, only then can levelling compounds be applied over the primer.

For extremely non porous, hard and tight substrates it is recommended that a light grind or sand be conducted to enhance adhesion.

MIXING:

Thoroughly mix primer before use.

CLEAN UP:

Clean all equipment with water immediately after use.

COVERAGE:

Approximately 5 to 10m² per litre.

INITIAL SET TIMES:

1-2 hours

CLEAN UP

Clean tools immediately after use with warm soapy water.

STORAGE

Keep in well ventilated areas stored out of direct sunlight.



UNIVERSAL PRIMER

CONTAINER SIZES

5 litre plastic containers

SAFETY & HANDLING

A Safety Data Sheet is available on request.

SHELF LIFE

12 -14 months in unopened containers stored out of direct sunlight.

DISPOSAL

Please dispose of empty containers and residue in accordance with your local waste management regulations.

FIRST AID

In use, please ensure that Occupational Health and Safety requirements are observed.

If swallowed, give plenty of water. Do not induce vomiting. Seek medical attention.

Skin: Wash off with warm water and soap.

Eyes: Irrigate with water for 10 minutes and see a doctor.

Restrictions:

Do not apply Universal Primer on substrates subject to rising damp.

Do not apply Universal Primer at thickness greater than 1 mm thick.

Do not apply Universal Primer on tiles that have a wax or excessively high gloss coating.

Note:

The supplied information is based on our experience and is to be regarded as general instructions. We cannot guarantee successful results as we do not have any influence on the conditions on site. In any case a test area is highly recommended before installation.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers. The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

Phone: 1800 242 931

Email: info@rlapolymers.com.au

Mail: 215 Colchester Road Kilsyth Victoria 3137 (attn Customer Services)

Australian Consumer Law

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage.

You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

Disclaimer

All Statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests.

Conditions of Sale contain a limited warranty against manufacturing defects.



Product:	UNIVERSAL PRIMER
Issue Date:	NOV 2018
Issue No:	DO2